

SATELLITE MULTISWITCHES

MODEL:SH131324E

DESCRIPTION:13x13x24 Satellite Multiswitch



Features:

- 12 satellite IF and 1 terrestrial TV inputs for 24 satellite receiver
- 12 satellite IF inputs selected by 13V、18V、22KHz and DisEqC 2.0 signal
- Low insertion loss, high isolation and return loss
- SAT-IF-PATHs to the subscribers are active and supplied by the receiver
- Sheet metal housing with plastic holder
- Design good for indoor usage

Specifications

| Item | Specifications | Typical | QC Limit | Remark |
|-----------------------|----------------|---------------------------------|----------|--------------|
| Frequency Range | | Terr.:47~862MHz SAT:950~2150MHz | | |
| Inputs | | 12 SAT+1 Terr. | | F connectors |
| Outputs | | 24 Receiver | | F connectors |
| Thru Loss | Terr. | 4dB | 5dB | |
| | SAT | 4dB | 5dB | |
| TAP Loss | Terr. | 6dB | 8dB | |
| | SAT | 5dB | 7dB | |
| Return Loss | Terr. | 12dB | 10dB | |
| | SAT | 12dB | 10dB | |
| Stop band attenuation | Terr. | 28dB | 25dB | |
| | SAT | 28dB | 25dB | |
| Isolation | H/V | 30dB | 25dB | |
| | REC-REC | 30dB | 25dB | |
| Power Adapter | | IN:100~240V OUT:18V 2000mA | | |
| Dimensions (L,W,H) | | 298x280x42 | | mm |