



Registered Design No.: ZL97 3 29666.6



www.tipa.eu

SPECIFICATIONS

Basic Functions	Range	Best Accuracy
DC Voltage	200mV/2000mV/20V/200V/300V	$\pm(1.5\%+2)$
AC Current	200V/300V	$\pm(2.5\%+15)$
DC Current	2000 μ A/20mA/200mA	$\pm(2.5\%+10)$
Resistance	200 Ω /2000 Ω /20k Ω /200k Ω /2000k Ω	$\pm(2.5\%+5)$
Special Functions		
Battery Test	1.5V, 9V	$\pm(2.5\%+2)$
Diode		
Square Wave Output		
Low Battery Display		
Input Impedance for DC Voltage Measurement	Around 1M Ω	
Max.Display	1999	

GENERAL CHARACTERISTICS

Power	12V Battery (A23)
LCD Size	31 x 13mm
Product Colour	Red and Grey
Product Net Weight	100g
Product Size	95 x 52 x 26mm
Standard Accessories	Test Lead, Battery, English Manual
Standard Individual Packing	Blister
Standard Quantity Per Carton	80 pcs
Standard Carton Measurement	560 x 370 x 302mm (0.063CBM Per Standard Carton)
Standard Carton Gross Weight	11.3kg

Specifications and other information are subject to change without further notice.