



Registered Design No.: 0211977.8M004



www.tipa.eu

SPECIFICATIONS

Basic Functions	Range	Best Accuracy
DC Voltage	400mV/4V/40V/400V/500V	$\pm(0.8\%+1)$
AC Voltage	4V/40V/400V/500V	$\pm(1.2\%+3)$
DC Current	400 μ A/4000 μ A/40mA/400mA/4A/10A	$\pm(1\%+2)$
AC Current	400 μ A/4000 μ A/40mA/400mA/4A/10A	$\pm(1.5\%+5)$
Resistance	400 Ω /4k Ω /40k Ω /400k Ω /4M Ω /40M Ω	$\pm(1\%+2)$
Special Functions		
Auto Ranging	✓	
Diode	✓	
Continuity Buzzer	✓	
Transistor	✓	
Low Battery Display	✓	
Input Impedance for DC Voltage Measurement	Around 10M Ω	
Max. Display	3999	

GENERAL CHARACTERISTICS

Power	1.5V Battery (AAA) \times 2
LCD Size	48 \times 16mm
Product Colour	Red and Grey
Product Net Weight	Around 156g
Product Size	130 \times 73.5 \times 35 mm
Standard Accessories	Test Lead, Battery, English Manual, Holster
Optional Accessories*	Clip-On Test Lead Light (UT-TL), Built-In Test Lead Light (UT-L1), Built-In Test Lead Light Plus (UT-L2)
Standard Individual Packing	Gift Box
Standard Quantity Per Carton	60 pcs
Standard Carton Measurement	Around 486 \times 345 \times 310 mm (Around 0.052 CBM Per Standard Carton)
Standard Carton Gross Weight	Around 18kg

*Available at Extra Cost

Specifications and other information are subject to change without further notice.