



Registered Design No.: 0412182.2M001

SPECIFICATIONS

Basic Functions	Range	Best Accuracy
DC Voltage	200mV/2V/20V/200V/1000V	$\pm(0.5\%+1)$
AC Voltage	2V/20V/200V/750V	$\pm(0.8\%+3)$
DC Current	20 μ A/200 μ A/2mA/20mA/200mA/10A	$\pm(0.8\%+1)$
AC Current	200 μ A/20mA/200mA/10A	$\pm(1\%+3)$
Resistance	200 Ω /2k Ω /20k Ω /200k Ω /2M Ω /200M Ω	$\pm(0.8\%+1)$
Capacitance	2 μ F	$\pm(4\%+3)$
Special Functions		
Diode	✓	
Continuity Buzzer	✓	
Transistor	✓	
Sleep Mode	✓	
Low Battery Display	✓	
Input Impedance for DC Voltage Measurement	10M Ω	
Max. Display	1999	

GENERAL CHARACTERISTICS

Power	9V Battery (6F22)
LCD Size	61 x 32 mm
Product Colour	UT39-Grey Holster-Red
Product Net Weight	Around 310g (Including Holster)
Product Size	172 x 83 x 38mm
Standard Accessories	Test Lead, Battery, English Manual, Holster
Optional Accessories*	Clip-On Test Lead Light (UT-TL), Built-In Test Lead Light (UT-L1), Built-In Test Lead Light Plus (UT-L2)
Standard Individual Packing	Gift Box
Standard Quantity Per Carton	40 pcs
Standard Carton Measurement	594 x 414 x 334mm (0.082CBM Per Standard Carton)
Standard Carton Gross Weight	Around 20.3kg

*Available at Extra Cost

Specifications and other information are subject to change without further notice.



www.tipa.eu