



Registered Design No.: 9911180, 1M001

## SPECIFICATIONS

Basic Functions	Range	Best Accuracy
DC Voltage	80mV/800mV/8V/80V/800V/1000V	$\pm(0.05\%+10)$
AC Voltage	800mV/8V/80V/800V/1000V	$\pm(0.8\%+20)$
DC Current	80mA/800mA/8A/10A	$\pm(0.2\%+40)$
AC Current	80mA/800mA/8A/10A	$\pm(0.5\%+40)$
Resistance	800 $\Omega$ /8k $\Omega$ /80k $\Omega$ /800k $\Omega$ /8M $\Omega$ /80M $\Omega$	$\pm(0.3\%+40)$
Conductance	80nS	$\pm(2\%+120)$
Capacitance	1nF/10nF/100nF/1 $\mu$ F/10 $\mu$ F/100 $\mu$ F	$\pm(2\%+3)$
Frequency	1kHz/10kHz/100kHz/1MHz	$\pm(0.02\%+1)$
Duty Cycle	1%~99.9%	
Special Functions		
Fused 10A Range		
Auto Ranging		
Diode		
Continuity Buzzer		
True RMS	AC	
Peak/Min/Max		
Max/Min/Avg		
Relative Mode		
Auto Data Hold		
RS232C		
Display Backlight		
Full Icon Display		
Sleep Mode		
Low Battery Display		
Input Impedance for DC Voltage Measurement	10M $\Omega$	
Max Display	79999 (frequency measurement counts 99999)	
Analog Bar Graph		

## GENERAL CHARACTERISTICS

Power	9V Battery (6F22)
LCD Size	62 x 53mm
Product Colour	UT70D-Grey, Holster - Red
Product Net Weight	600g (including holster)
Product Size	195 x 90 x 40mm
Standard Accessories	Test Lead, Battery, English Manual, Test Clip, RS232C Interface Cable, Software, Holster
Optional Accessories*	Clip-On Test Lead Light (UT-TL), Built-In Test Lead Light (UT-L1), Built-In Test Lead Light Plus (UT-L2), Carrying Bag
Standard Packing	Gift Box
Standard Quantity Per Carton	20 pcs
Standard Carton Measurement	535 x 365 x 380mm (Around 0.074 CBM Per Standard Carton)
Standard Carton Gross Weight	22.7kg



www.tipa.eu

\*Available at Extra Cost

Specifications and other information are subject to change without further notice.