



## SPECIFICATIONS

Basic Functions	Range	Best Accuracy
DC Voltage	200mV/2V/20V/200V/1000V	±(0.05%+5)
AC Voltage	2V/20V/200V/1000V	±(0.6%+40)
DC Current	200µA/2000µA/20A/200mA/10A	±(0.1%+15)
AC Current	200µA/2000µA/20A/200mA/10A	±(0.8%+15)
Resistance	200Ω/2kΩ/20kΩ/200kΩ/2MΩ/20MΩ	±(0.4%+20)
Capacitance	20nF/200nF/2µF/20µF/200µF/2mF/20mF	±(1.2%+20)
Temperature (°C)	-40°C ~ 1000°C	±(1%+30)
Temperature (°F)	-40°F ~ 1832°F	±(1.5%+50)
Frequency	20Hz/200Hz/2kHz/20kHz/200kHz/2MHz/20MHz/200MHz	±(0.1%+15)
Duty Cycle	10%~90%	±(1%+30)
4~20mA Loop	0~100%	±(1%+50)
<b>Special Functions</b>		
Fused 10A Range		✓
Auto Ranging		✓
Current Measurement Alarm		✓
Function Set Up		✓
Voltage & Current : AC + DC Measurement		✓
Data Logging		100
Data Recall		✓
Diode		✓
Continuity Buzzer		✓
True RMS		✓
Peak Hold		✓
Max/Min Mode		✓
Relative Mode		✓
Data Hold		✓
USB		✓
Double Display Backlight		✓
Full Icon Display		✓
Sleep Mode		✓
Low Battery Display		✓
Input Impedance for DC Voltage Measurement	DC 200mV : Around 2.5GΩ All Other Ranges : 10MΩ	✓
Max. Display	20000	✓
Analogue Bar Graph		✓

## GENERAL CHARACTERISTICS

Power	9V Battery (6F22)
LCD Size	73 × 50 mm
Product Colour	Red and Grey
Product Net Weight	384g
Product Size	200 × 93 × 40mm
Standard Accessories	Test Lead, Battery, English Manual, Point Contact Temperature Probe, Alligator Clip, Test Clip, USB Interface Cable, Software, Carrying Bag
Optional Accessories*	Clip-On Test Lead Light (UT-TL), Built-In Test Lead Light (UT-L1), Built-In Test Lead Light Plus (UT-L2)
Standard Individual Packing	Gift Box
Standard Quantity Per Carton	20 pcs
Standard Carton Measurement	542 × 376 × 388mm (0.079 CBM Per Standard Carton)
Standard Carton Gross Weight	19kg