



Registered Design No.: 0211977.6M001

SPECIFICATIONS

Basic Functions	Range	Best Accuracy
DC Voltage	200mV/2V/20V/200V/1000V	±(0.5%+5)
AC Voltage	2V/20V/200V/750V	±(0.8%+5)
DC Current	200mA/10A	±(0.8%+5)
Resistance	200Ω/2kΩ/20kΩ/200kΩ/2MΩ/20MΩ	±(0.8%+5)
Special Functions		
Fused 10A Range		✓
Dwell	4Cyl/8Cyl/8Cyl	±(3%+5)
Tach	4Cyl/8Cyl/8Cyl	±(3%+5)
Diode		✓
Continuity Buzzer		✓
Data Hold		✓
Full Icon Display		✓
Low Battery Display		✓
Input Impedance for DC Voltage Measurement	Around 10MΩ	✓
Max. Display	1999	✓

GENERAL CHARACTERISTICS

Power	9V Battery (6F22)
LCD Size	60 x 54 mm
Product Colour	UT105 - Grey, Holster - Red
Product Net Weight	Around 351g (including holster)
Product Size	179 x 88 x 39 mm
Standard Accessories	Test Lead, Battery, English Manual, Holster
Optional Accessories*	Clip-On Test Lead Light (UT-TL), Built-In Test Lead Light (UT-L1), Built-In Test Lead Light Plus (UT-L2), Alligator Clip (41600720)
Standard Individual Packing	Gift Box
Standard Quantity Per Carton	30 pcs
Standard Carton Measurement	508 x 433 x 326 mm (0.072 CBM Per Standard Carton)
Standard Carton Gross Weight	Around 22kg



www.tipa.eu

*Available at Extra Cost

Specifications and other information are subject to change without further notice.