



Basic Functions	Range	Best Accuracy
DC Voltage	400mV/4V/40V/400V/600V	±(0.8%+1)
AC Voltage	4V/40V/400V/600V	±(1.2%+5)
AC Current	400A/1000A	±(1.5%+5)
Resistance	400Ω/4kΩ/40kΩ/400kΩ/4MΩ/40MΩ	±(1%+2)
Frequency	10Hz~10MHz	±(0.1%+3)
Duty Cycle	0.1%~99.9%	For reference only
Special Functions		
Diode	✓	
Continuity Buzzer	✓	
Data Hold	✓	
Display Backlight	✓	
Full Icon Display	✓	
Sleep Mode	✓	
Low Battery Display	✓	
Input Impedance for DC Voltage Measurement	10MΩ	
Max. Display	3999	

GENERAL CHARACTERISTICS

Power	9V Battery (6F22)
LCD Size	18 x 36.5 mm
Product Colour	Red and Grey
Product Net Weight	350g
Product Size	236 x 97 x 40mm
Standard Accessories	Test Lead, Battery, English Manual, Vinyl Bag
Standard Individual Packing	Gift Box
Standard Quantity Per Carton	20 pcs
Standard Carton Measurement	530 x 360 x 385mm (0.0735 CBM Per Standard Carton)
Standard Carton Gross Weight	Around 12kg