



Registered Design No.: 0011438. 1M001

SPECIFICATIONS

Basic Functions	Range	Best Accuracy
DC Voltage	400mV/4V/40V/400V/600V	±(0.8%+1)
AC Voltage	4V/40V/400V/600V	±(1.2%+5)
AC Current	400A/1000A	±(2%+5)
Resistance	400Ω/4kΩ/40kΩ/400kΩ/4MΩ/40MΩ	±(1%+2)
Capacitance	4nF/40nF/400nF/4μF/40μF/200μF	±(3%+5)
Temperature(°C)	-40°C~1000°C	±(1%+3)
Frequency	10Hz ~ 10MHz	±(0.1%+3)
Duty Cycle	0.1% - 99.9%	✓
Special Functions		
Auto Ranging		✓
Diode		✓
Continuity Buzzer		✓
Relative Mode		✓
Data Hold		✓
Display Backlight		✓
Full Icon Display		✓
Sleep Mode		✓
Jaw Opening Light		✓
Max. Jaw Size	40mm	✓
Low Battery Display		✓
Input Impedance for DC Voltage Measurement	Around 10MΩ	✓
Max. Display	3999	✓

GENERAL CHARACTERISTICS

Power	9V Battery (6F22), 3V Battery (AAA×2)
LCD Size	52 × 27 mm
Product Colour	Body-Grey, Jaw-Red
Product Net Weight	540g (excluding tool box)
Product Size	260 × 90 × 45 mm
Standard Accessories	Test Lead, English Manual, Batteries, Point Contact Temperature Probe, Tool Box
Optional Accessories*	Clip-On Test Lead Light(UT-TL), Built-In Test Lead Light(UT-L1), Built-In Test Lead Light Plus(UT-L2), Carrying Bag
Standard Packing	Gift Box
Standard Quantity Per Carton	20 pcs
Standard Carton Measurement	591 × 370 × 474 mm (0.104 CBM Per Standard Carton)
Standard Carton Gross Weight	27.6kg

*Available at Extra Cost

Specifications and other information are subject to change without further notice.



www.tipa.eu