

SPECIFICATIONS



CE

Basic Functions	Range	Best Accuracy
DC Voltage	400mV/4V/40V/400V/600V	$\pm(0.8\%+1)$
AC Voltage	4V/40V/400V/600V	$\pm(1.2\%+5)$
AC Current	400A/1000A	$\pm(1.5\%+5)$
Resistance	400 Ω /4k Ω /40k Ω /400k Ω /4M Ω /40M Ω	$\pm(1\%+2)$
Temperature ($^{\circ}\text{C}$)	-40 $^{\circ}\text{C}$ ~1000 $^{\circ}\text{C}$	$\pm(2\%+8)$
Frequency	10Hz~10MHz	$\pm(0.1\%+3)$
Special Functions		
Diode	✓	
Continuity Buzzer	✓	
Relative Mode	✓	
Data Hold	✓	
Display Backlight	✓	
Full Icon Display	✓	
Sleep Mode	✓	
Low Battery Display	✓	
Input Impedance for DC Voltage Measurement	10M Ω	
Max. Display	3999	

GENERAL CHARACTERISTICS

Power	9V Battery (6F22)
LCD Size	18 x 36.5 mm
Product Colour	Red and Grey
Product Net Weight	350g
Product Size	236 x 97 x 40mm
Standard Accessories	Test Lead, Battery, English Manual, Point Contact, Temperature Probe, Vinyl Bag
Standard Individual Packing	Gift Box
Standard Quantity Per Carton	20 pcs
Standard Carton Measurement	530 x 360 x 385mm (0.0735 CBM Per Standard Carton)
Standard Carton Gross Weight	Around 12kg



www.tipa.eu