



SPECIFICATIONS

Basic Functions	Range	Best Accuracy
Insulation Resistance	0.5MΩ ~100GΩ	±(3%+5)
Testing Voltage	500V/1000V/1500V/2500V	0~20%
DC Voltage	600V	±(2%+5)
AC Voltage	600V	±(2%+5)
Special Functions		
Auto Ranging		✓
Short Circuit Current		<1.8mA
Data Logging		18
Data Recall		✓
Sleep Mode		✓
Polarization index (PI)		✓
Dielectric Absorption (DAR)		✓
Timer	Around 15 minutes	✓
Compare		✓
Battery Display		✓
White Display Backlight		✓
Over Range and High Voltage Warning		✓
USB		✓
Max. Display	9999	✓
Analogue Bar Graph		✓

GENERAL CHARACTERISTICS

Power	1.5V Alkaline Battery(LR14)×8
LCD Size	123 mm x 58 mm
Product Color	Red and Grey
Product Net Weight	1.8Kg
Product Size	202×155×94mm
Standard Accessories	2 pcs of one plug test lead to one alligator clip (black and Green), 1pc of two plugs test lead to one alligator clip (Red), Batteries, English Manual , Tool Box, USB Interface Cable, Software
Optional Accessories*	Power Adapter
Standard Individual Packing	Gift Box
Standard Quantity Per Carton	4 pcs
Standard Carton Measurement	525 × 335 × 345mm (0.061 CBM Per Standard Carton)
Standard Carton Gross Weight	18kg

*Available at Extra Cost

Specifications and other information are subject to change without further notice.