



CE



SPECIFICATIONS

| Basic Functions | Range | Best Accuracy |
|---------------------|-----------------------------------------|---------------|
| Resistance | 20Ω/200Ω/2kΩ/20kΩ/200kΩ/2MΩ/20MΩ/2000MΩ | ±(0.8%+1) |
| Inductance | 2mH/20mH/200mH/2H/20H/200H | ±(2%+8) |
| Special Functions | | |
| Diode | | ✓ |
| Continuity Buzzer | | ✓ |
| Transistor | | ✓ |
| Data Hold | | ✓ |
| Low Battery Display | | ✓ |
| Max. Display | 1999 | ✓ |

GENERAL CHARACTERISTICS

| | |
|------------------------------|-----------------------------------------------------|
| Power | 9V Battery (6F22) |
| LCD Size | 61 × 32 mm |
| Product Colour | Grey Holster-Red |
| Product Net Weight | 310g |
| Product Size | 172 × 83 × 38mm |
| Standard Accessories | Test Clip, Battery, English Manual, Holster |
| Standard Individual Packing | Gift Box |
| Standard Quantity Per Carton | 40 pcs |
| Standard Carton Measurement | 598 × 418 × 340mm (0.085CBM Per Standard Carton) |
| Standard Carton Gross Weight | 21kg |