

NVF4-3 & NVF4-4



NVF4-3
29×29×26.5



NVF4-4
29×29×26.5(+16)

Features	
<ul style="list-style-type: none"> Small size. Contact load capacity up to 80A. Suitable for automobile. PC board mounting and direct insert mounting available. 	

Ordering Information	
NVF4-3 C Z 30 b DC12V C D 1 2 3 4 5 6 7 8	
1 Part number: NVF4-3, NVF4-4 (Insulation Bracket), NVF4-4a (Metal Bracket) 2 Contact arrangement: A:1A; B:1B; C:1C; U:1U 3 Enclosure: S: Sealed type; Z: Dust cover; 4 Contact current: A Form:50A,80A; B Form:40A,70A; C Form:40,50A,70A,80A; U Form:2×25A	5 Terminals: b: PCB type; a: plug in type 6 Coil rated voltage(V): DC:6,12,24 7 Contact material: C:AgCdO; N:AgNi; NIL: AgSnO ₂ 8 Coil transient suppression: D: with diode.; 2D:with two diodes.; R: with resistance.; DR: with diode and resistance; NIL: standard

Contact Data											
Contact Arrangement	1A (SPSTNO) , 1B (SPSTNC) ,1C (SPDT(B-M)) ,1U (SPSTNODM)										
Contact Material	AgSnO ₂ , AgNi, AgCdO										
Contact Rating (resistive)	<table border="1"> <tr> <th></th> <th>1A</th> <th>1B</th> <th>1C</th> <th>1U</th> </tr> <tr> <td></td> <td>50A,80A/14VDC</td> <td>40A,70A/14VDC</td> <td>NO:50A,80A/14VDC NC:40A,70A/14VDC</td> <td>2×25A/14VDC</td> </tr> </table>		1A	1B	1C	1U		50A,80A/14VDC	40A,70A/14VDC	NO:50A,80A/14VDC NC:40A,70A/14VDC	2×25A/14VDC
	1A	1B	1C	1U							
	50A,80A/14VDC	40A,70A/14VDC	NO:50A,80A/14VDC NC:40A,70A/14VDC	2×25A/14VDC							
Max. Switching Power	980W										
Max. Switching Voltage	75VDC										
Contact Resistance or Voltage drop	≤30mΩ										
Operation life	<table border="1"> <tr> <th></th> <th>Electrical</th> <th>Mechanical</th> </tr> <tr> <td></td> <td>10⁵</td> <td>10⁷</td> </tr> </table>		Electrical	Mechanical		10 ⁵	10 ⁷				
	Electrical	Mechanical									
	10 ⁵	10 ⁷									

Coil Parameter								
Dash numbers	Coil voltage VDC		Coil resistance Ω ±10%	Pickup voltage VDC(max) (65%of rated voltage)	Release voltage VDC(min) (10% of rated voltage)	Coil power consumption W	Operate Time ms	Release Time ms
	Rated	Max.						
006-1800	6	7.8	20	3.9	0.6	1.8	≤7	≤5
012-1800	12	15.6	80	7.8	1.2			
024-1800	24	31.2	320	15.6	2.4			

CAUTION: 1.The use of any coil voltage less than the rated coil voltage will compromise the operation of the relay.
2.Pickup and release voltage are for test purposes only and are not to be used as design criteria.

Operation condition

Insulation Resistance ¹⁾	100MΩ min(at 500VDC)	Item7 of IEC61810-5
Dielectric Strength ¹⁾		
Between contacts	50Hz 500V	Item 6 of IEC 61810-5
Between contact and coil	50Hz 500V	Item 6 of IEC 61810-5
Shock resistance	147m/s ² 11ms	IEC68-2-27 Test Ea
Vibration resistance	10~40Hz double amplitude 1.5mm	IEC68-2-6 Test Fc
Terminals strength	8N 4N(PC type)	IEC68-2-21 TestUa 2
Solderability	235°C ±2°C 3±0.5s	IEC68-2-20 TestTamethod 1
Ambient Temperature	-40~125°C	
Relative Humidity	85% (at 40°C)	IEC68-2-3 TestCa
Mass	46g(NVF4-3);48g(NVF4-4)	

Note: 1). When testing, coil terminals should be connected, If coil transient suppression is installed in relay .

Dimensions

mm / inch

40A, 50A PCB mode 70A, 80A PCB 式

Note: Terminals as shown above are also available.

Dimensions

Plug in type 40A, 50A PCB type 70A, 80A PCB type

Wiring diagram (Bottom view)

1A 1B 1C 1U

NOTES 1).Dimensions are in millimeters.
2).Inch equivalents are given for general information only.

Reference Data

