

Thermal fuse 2A / Bezpieczniki termiczne 2A



■ 2A/250V_{AC}

| Symbol | T _f (°C) | T _a (°C) | T _h (°C) | T _m (°C) |
|----------|---------------------|---------------------|---------------------|---------------------|
| BT075/02 | 75 | 72±1 | 55 | 130 |
| BT076/02 | 76 | 73±1 | 55 | 130 |
| BT080/02 | 80 | 75±2 | 58 | 130 |
| BT085/02 | 85 | 80±2 | 62 | 130 |
| BT090/02 | 90 | 85±2 | 65 | 130 |
| BT095/02 | 95 | 90±1 | 68 | 130 |
| BT098/02 | 98 | 96±1 | 70 | 130 |
| BT100/02 | 100 | 97±1 | 72 | 130 |
| BT102/02 | 102 | 98±1 | 72 | 150 |
| BT110/02 | 110 | 105±1 | 80 | 150 |
| BT115/02 | 115 | 111±2 | 87 | 150 |
| BT120/02 | 120 | 115±1 | 90 | 150 |
| BT126/02 | 126 | 121±2 | 95 | 150 |
| BT130/02 | 130 | 126±1 | 102 | 150 |
| BT133/02 | 133 | 130±1 | 103 | 150 |
| BT136/02 | 136 | 131±1 | 105 | 150 |
| BT140/02 | 140 | 136±1 | 110 | 160 |
| BT145/02 | 145 | 140±1 | 114 | 180 |
| BT150/02 | 150 | 146±1 | 120 | 180 |