

Specifications


ModelNO .		JTX5L-BS
Nominal Voltage		12V
RatedCapacity(10 hours rate)		5Ah
Dimensions	Length	113mm (4.44 inches)
	Width	70mm (2.75 inches)
	Height	106mm (4.17 inches)
	TotalHeight	106mm (4.17 inches)
Approx. Weight		1.70kg (3.74 Lbs) ± 3%
ChargeCurrent(A)	0.5 A (14.4V constant voltage charge)	

Characteristics

Capacity25°C (77°F)	10hours rate(0.5A to 10.5V)	5.0Ah
	5hours rate(0.85A to 10.2V)	4.3Ah
	1C (5.0A to 9.60V)	2.3Ah
	3C (15.0A to 9.60V)	1.8Ah
Cranking Amperes(by Midtronic Tester)		155A
Cold Cranking Amperes(-18°C SAE Standard)		65A
Cold Cranking Amperes(-18°C EN Standard)		65A
Internal Resistance(at 1KHz)		Approx.17.8(mΩ/25°C ± 15%)
Operating Temperature Range	Charge	0°C (32°F) to 40°C (104°F)
	Discharge	-30°C (-22°F) to 50°C (122°F)
	Storage	-15°C (5°F) to 40°C (104°F)
LifeExpectancy (Cycle Use)	60% depth of discharge 250 cycles	
	30% depth of discharge 400 cycles	
ChargeRetention (self-discharge life) at 20°C (68°F)	1 month	97%
	3 month	90%
	6 month	80%
Warranty	1 year	
CaseMaterial	ABS	



Dimensions



Discharge Time VS. Discharge Current (25°C)

