



heat-shrinkable tube (color and transparent)

Material: PEVA

№	Denomination	As delivered		After shrinkage		Recommended range of wire diameters, mm	Tube length L, m ((± 2 mm))
		D, mm	W, mm	d, mm	W, mm		
1	DRS-1,5	2,00±0,2	0,18±0,05	0,85	0,36±0,1	0,95 - 1,4	1
2	DRS-1	1,5±0,20	0,18±0,05	0,65	0,36±0,1	0,75 - 0,9	1
3	DRS-10	10,5±0,3	0,28±0,05	5,0	0,56±0,1	5,2 - 9,0	1; 2
4	DRS-12	12,5±0,3	0,28±0,05	6,0	0,56±0,1	6,2 - 11,0	1; 2
5	DRS-14	14,5±0,3	0,35±0,05	7,0	0,7±0,1	7,3 - 13,0	1
6	DRS-16	16,5±0,4	0,35±0,05	8,0	0,7±0,1	8,3 - 15,0	1
7	DRS-18	19,0±0,5	0,35±0,05	9,0	0,7±0,1	9,3 - 17,0	1
8	DRS-2	2,5±0,2	0,225±0,05	1,0	0,45±0,1	1,1 - 1,8	1; 2
9	DRS-20	22,0±0,5	0,4±0,08	10,0	0,8±0,15	10,4 - 19,0	1
10	DRS-22	24,0±0,5	0,4±0,08	11,0	0,8±0,15	11,4 - 21,0	1
11	DRS-25	26,0±0,5	0,45±0,08	12,5	0,9±0,15	12,8 - 24,0	1
12	DRS-28	29,0±0,5	0,45±0,08	14,0	0,9±0,15	14,4 - 27,0	1
13	DRS-3	3,5±0,2	0,225±0,05	1,5	0,45±0,1	1,6 - 2,7	1; 2
14	DRS-30	31,5±1,0	0,5±0,08	15,0	1,0±0,15	16,0 - 29,0	1
15	DRS-35	36,5±1,0	0,5±0,08	17,5	1,0±0,15	18,0 - 34,0	1
16	DRS-4	4,7±0,2	0,225±0,05	2,0	0,45±0,1	2,1 - 3,6	1; 2
17	DRS-40	41,5±1,0	0,5±0,08	20,0	1,0±0,15	21,0 - 39,0	1
18	DRS-45	46,5±1,5	0,5±0,1	22,5	1,0±0,2	23,5 - 44,0	1
19	DRS-5	5,5±0,2	0,28±0,05	2,5	0,56±0,1	2,6 - 4,5	1; 2
20	DRS-50	≥50,0	0,55±0,1	25,0	1,10±0,2	26,0 - 49,0	1
21	DRS-6	6,5±0,2	0,28±0,05	3,0	0,56±0,1	3,1 - 5,4	1; 2
22	DRS-60	≥60,0	0,6±0,08	30,0	1,2±0,15	35,0 - 55,0	1
23	DRS-8	8,5±0,3	0,28±0,05	4,0	0,56±0,1	4,2 - 7,2	1; 2

Notice – Tubes of seven colors: white, yellow, yellow-green, green, red, blue, black.