

Solenoid Valve Specifications

1. Water Inlet Solenoid Valve

Standard Voltage: DC12V, DC24V, AC220V

Corresponding Current Power: 4.8W

Pressure Range: 0.02–0.8MPa

Operation Type: Pilot-operated

Applicable Medium: Water Fluid Temperature: 0–80°C

Ambient Temperature: 0–60°C

Valve Port Size

2. Normally Open Water Inlet Solenoid Valve

Standard Voltage: DC12V, DC24V, AC220V

Corresponding Current Power: 4.8W

Pressure Range: 0.02–0.8MPa

Operation Type: Pilot-operated

Applicable Medium: Water Fluid

Temperature: 0–80°C

Ambient Temperature: 0–60°C

Valve Port Size

3. Zero-pressure Drainage Solenoid Valve

Standard Voltage: DC12V, DC24V, AC220V

Corresponding Current Power: 4.8W

Pressure Range: 0–0.005MPa

Pressure Range: 0–0.3MPa (Enhanced Version)

Operation Type: Direct-acting

Applicable Medium: Water

Fluid Temperature: 0–80°C

Ambient Temperature: 0–60°C

Valve Port Size

4. Zero-pressure Drainage Diaphragm Solenoid Valve

Standard Voltage: DC12V, DC24V, AC220V

Corresponding Current Power: 8W

Pressure Range: 0–0.005MPa Operation Type: Direct-acting

Applicable Medium: Water

Fluid Temperature: 0–80°C

Ambient Temperature: 0–60°C

Valve Port Size

