

OFF GRID SOLAR INVERTER

MKS SERIES

On/Off Grid Solar Inverter



Max. Efficiency
98%



IP21
Ingress Protection



40A MPPT



DUSTPROOF



Receptacle



LCD Display



»» Features

- Pure sine wave solar inverter
- Built-in 40A MPPT Solar charger
- PV input voltage range 20~150VDC (for 1000W), 30~150VDC (for 1500W)
- Built-in anti-dust kit for harsh environment
- Smart battery charge design to optimize battery life
- Meet rich customized demands
- Solar energy is provided directly to the load first

»» Product Data Sheet

Model	MKS-1000-12	MKS-1500-24
RATED POWER	1000W/1000VA	1500W/ 1500VA
AC Input		
Voltage	230VAC	
Selectable Voltage Range	170~280VAC(For Personal Computers)	
	90~280VAC(For Home Appliances)	
Frequency Range	50 Hz/60Hz(Auto sensing)	
AC OUTPUT		
AC Voltage Regulation	230VAC±5%	
Surge Power	2000 VA	30 00VA
Efficiency(Peak)PV to INV	98%	
Efficiency(Peak)Battery to INV	94%	
Transfer Time	10 ms	
BATTERY		
Battery Voltage	12VDC	24VDC
Floating Charge Voltage	13.5VDC	27VDC
Overcharge Protection	16VDC	32VDC
SOLAR CHARGER & AC CHARGER		
Solar Charger Type	MPPT	
Maximum PV Array Power	600W	1200W
MPPT Range @ Operating Voltage	20~150VDC	30~150VDC
Maximum PV Array Open Circuit Voltage solar	150VDC	
Maximum Solar Charging Current	40A	
Maximum AC Charging Current	40A	
Maximum Solar+AC Charging Current	80A	
PHYSICAL		
Dimension,D*W*H(mm)	290*240*91	
Carton Dimension,D X W XH(mm)	340*295*145	
Net Weight(kgs)	3.5	3.6
Gross Weight(kgs)	4.0	4.2
ENVIRONMENT		
Humidity	5% to 95% Relative Humidity (Non ~ condensing)	
Operating Temperature	-10°C ~ 50 °C	
STANDARD		
Compliance Safety	CE	