

Range Summary

Using oxygen recombination technology: maintenance-free

PbCaSn alloy for plate grids: low self discharge rate than 3% per month

High quality AGM separator: extend cycle life and prevent micro short circuit retardant

High purity raw material: 99.99% pure lead

Application

Cable Television
Communication
Equipment
Security System

UPS
Control Equipment
Medical Equipment
Emergency Power



ISO 9001




ISO 14001




CE

Battery Dimensions




Terminal Dimensions



Technical Specifications

Battery Model	VT6-12			
Designed Floating Life	5 Years			
Capacity(25°C)	20HR(0.6A, 1.80V)	10HR(1.08A, 1.80V)	5HR(2.04A, 1.75V)	1HR(7.85A, 1.60V)
	12AH	10.8AH	10.2AH	7.85AH
Dimensions	Length	Width	Height	Total Height
	151mm(5.94inch)	50mm(1.97inch)	94mm(3.70inch)	100mm(3.94inch)
Approx. Weight	1.71Kg			
Internal Resistance	Full charged at 25°C: 0.010 Ohm			
Self Discharge	3% of capacity declined per month at (25°C)			
Capacity Affected by Temp.(20HR)	40°C	25°C	0°C	-15°C
	109%	100%	85%	65%
Charge Voltage(25°C)	Cycle use		Float use	
	7.2-7.5V(-15mV/ °C), max. Current: 3.6A		6.8-6.9V(-10mV/ °C)	

General purpose application series



Constant current discharge ratings-amperes at 25°C

F.V/T in e	5 M IN	10 M IN	15 M IN	30 M IN	1 H R	3 H R	5 H R	10 H R	20 H R
1.60V	46.9	29.2	22.0	13.4	7.85	3.74	2.17	1.13	0.67
1.67V	44.0	27.7	21.2	12.8	7.74	3.60	2.13	1.12	0.64
1.70V	40.3	26.7	20.7	11.7	7.51	3.36	2.08	1.11	0.63
1.75V	39.5	25.8	20.0	11.1	7.15	3.25	2.04	1.10	0.62
1.80V	35.4	24.7	18.2	10.3	6.70	3.12	1.92	1.08	0.60
1.85V	31.2	23.5	16.3	9.45	6.24	3.01	1.79	1.07	0.58

Constant power discharge ratings-watts at 25°C

F.V/T in e	5 M IN	10 M IN	15 M IN	30 M IN	1 H R	3 H R	5 H R	10 H R	20 H R
1.60V	82.2	52.7	40.2	24.2	14.2	6.64	3.67	2.25	1.33
1.67V	79.4	51.3	39.7	23.7	14.1	6.43	3.66	2.24	1.28
1.70V	75.2	50.8	39.3	22.2	13.8	6.14	3.61	2.22	1.27
1.75V	74.7	50.7	39.0	21.5	13.6	6.00	3.58	2.20	1.24
1.80V	68.8	49.9	36.2	20.5	12.8	5.82	3.47	2.17	1.20
1.85V	62.4	47.4	32.8	19.2	12.0	5.65	3.36	2.14	1.16

Quality Management System Authentication GB/T19001-2008 NO.00113Q29865ROM/4200	CE authentication CE12-GPE 120171	        
---	--------------------------------------	--

WUHAN VUTION LITHIUM POWER TECHNOLOGY CO.,LTD

Tel: +86-712-8371 688

Mail: sales13@vutionlithium.com

ADD:24th Floor,Optics Valley Dingchuang International,Optics

Fax: +86-712-879 0888

Web: www.vutionlithium.com

Valley Rare Eco Industrial Park,Wuhan,Hubei Province,China