

S-350W



CASE:P16-8 215×115×50mm

terminal 9x9.5mm

L , N : AC



-V : DC

+V : DC

| | |
|-------------------------|---|
| AC input voltage range | 85-132VAC/170-264VAC 47-63Hz 240-370VDC |
| Input current | 6.5A/115V 4A/230V |
| AC inrush current | Cold-start current 25A/115V 50A/230V |
| Leakage current | <3.5mA/240VAC |
| DC adjustable range | ±10% rated output voltage |
| Over load protection | 105-135% hiccup mode,auto-recovery |
| Over-voltage protection | 115-135% |
| Setup rise hold up time | 2000ms 50ms 20ms |
| Withstand voltage | I/P-O/P: 1.5KVAC 1minute I/P-FG: 1.5KVAC 1minute O/P-O/P: 0.5KVAC 1minute |
| Working temperature | -10 ~ +60 .20%-90% RH |
| Weight/packing | 1.15kg.24pcs/27.6kg |

| type | Output | Error | Range | Efficiency |
|------------|-----------------|-------|-------|------------|
| S-350-5 | 5V , 0-50A | ±2% | 150mV | 73% |
| S-350-7.5 | 7.5V , 0-40A | ±2% | 150mV | 76% |
| S-350-12 | 12V , 0-29A | ±1% | 150mV | 74% |
| S-350-13.5 | 13.5V , 0-25.8A | ±1% | 150mV | 79% |
| S-350-15 | 15V , 0-23.2A | ±1% | 150mV | 78% |
| S-350-24 | 24V , 0-14.6A | ±1% | 150mV | 81% |
| S-350-27 | 27V , 0-13A | ±1% | 200mV | 82% |
| S-350-48 | 48V , 0-7.3A | ±1% | 240mV | 83% |

