

General Series battery

JYC General (GP) Series VRLA batteries are designed with AGM (Absorbent Glass Mat) technology, High performance plates and electrolyte to give extra power output for common power backup system. GP Series Batteries are the general purpose batteries with 10 years floating design life at 25°C, Meet with IEC,BS,JIS and Eurobat standard,UL(MH62092),CE approved.

Application

- * Emergency Power System
- * Communication equipment
- * Telecommunication systems
- * Uninterruptible power supplies
- * Electric toy car and wheelchairs, etc.
- * Power tools
- * Alarm system
- * Marine equipment
- * Medical equipment
- * Fire and Security System



General Features

- * Heavy Duty Grid
- * Mechanized assembly
- * Non-spillable construction
- * High Reliability and Stability
- * Sealed and Maintenance-free
- * Long Life and low self-discharge design


Construction

- * Positive Lead dioxide
- * Electrolyte . . . Sulfuric acid
- * Separator . . . Fiber glass
- * Container ABS(UL94-HB) / Flame Retardant ABS (UL94-V0)
- * Negative Lead
- * Safety Valve . . . EPDR
- * Terminal Copper

Specification

Battery Model	Nominal Voltage		12V (6 cells per unit)	
	Rated capacity (10 Hour rate)		55Ah	
Dimension	Length	Width	Height	Total Height
	230mm (9.05 inches)	139mm (5.47 inches)	210mm (8.27 inches)	215mm (8.46 inches)
Approx Weight	15.30kg(33.73lbs) ± 3%			
Internal Resistance	Full charged at 25°C(77°F):Approx 6.90mΩ			
Maximum Charge Current	16.5A			
Max.discharge current	550A (5Sec.)			
Short-circuit current	1000A			
Operating Temperature Range	Nominal Operating Temperature	Discharge	Charge	Storage
	25°C(77°F)	-15°C~ 50°C (5°F~122°F)	-15°C~ 40°C (5°F~104°F)	-15°C~ 40°C (5°F~104°F)
Capacity @ 25°C (77°F)	10 hour rate(5.5A,10.8V)	5 hour rate(9.50A,10.5V)	3 hour rate(14.57A,10.2V)	1 hour rate(34.10A,9.6V)
	55.0Ah	47.5Ah	43.7Ah	34.1Ah
Capacity affected by Temp.(10HR)	40°C (104°F)	25°C (77°F)	0°C (32°F)	-15°C (5°F)
	102%	100%	85%	65%
Charge method at 25°C(77°F)	Float Charging Voltage	Equalization Charging Voltage	Cycle Use Voltage	
	13.5~13.8 VDC (-3mV/cell/°C)	14.1~14.4 VDC (-4mV/cell/°C)	14.4~15.0 VDC (-5mV/cell/°C)	

Outer dimension (mm)




Terminal Type


Constant Current(Amp) and Constant Power(Watt) Discharge Table at 25°C(77°F)

F.V/Time		5min	10min	15min	20min	30min	1h	2h	3h	5h	8h	10h	20h
1.85V/cell	A	117	88	70.7	60.0	52.0	31.5	19.50	14.10	9.30	6.50	5.40	2.86
	W	219	166	134	115	101	61.7	38.31	27.79	18.38	12.88	10.80	5.75
1.80V/cell	A	137	98	77.0	64.5	53.2	32.2	19.80	14.26	9.40	6.59	5.50	2.90
	W	254	184	146	123	104	62.9	38.76	28.07	18.60	13.04	10.95	5.82
1.75V/cell	A	152	108	84.0	69.0	54.3	32.8	20.08	14.41	9.50	6.67	5.55	2.94
	W	281	202	157	132	105	63.7	39.03	28.22	18.74	13.20	11.02	5.86
1.70V/cell	A	167	117	89.0	73.5	55.5	33.4	20.38	14.57	9.59	6.74	5.61	2.97
	W	306	218	168	139	107	64.5	39.50	28.39	18.83	13.29	11.06	5.90
1.67V/cell	A	175	121	92.0	75.5	56.0	33.7	20.45	14.62	9.64	6.77	5.62	2.99
	W	319	225	172	143	107	64.9	39.46	28.41	18.85	13.31	11.07	5.92
1.60V/cell	A	187	130	98.0	79.0	57.0	34.1	20.70	14.70	9.70	6.80	5.64	3.00
	W	338	242	184	149	108	65.4	39.81	28.43	18.89	13.33	11.08	5.93


Discharge characteristic curve (25°C/77°F)




Charging characteristic curve of floating charge (25°C/77°F)




Cycle service life in relation to depth of discharge




Cyclic charging characteristic curve (25°C/77°F)




Relationship between temperature and capacity



Relationship between charging voltage and temperature



Self discharge characteristics



Temperature vs Float Life

